

NCS2511

1 GHz Current Feedback Op Amp

NCS2511 is a 1 GHz current feedback monolithic operational amplifier featuring high slew rate and low differential gain and phase error. The current feedback architecture allows for a superior bandwidth and low power consumption.

Features

- -3.0 dB Small Signal BW ($A_V = +2.0$, $V_O = 0.5 V_{P-P}$) 1 GHz Typ
- Slew Rate 2500 V/ μ s
- Supply Current 7.5 mA
- Input Referred Voltage Noise 5.0 nV/ $\sqrt{\text{Hz}}$
- THD -67 dB ($f = 5.0$ MHz, $V_O = 2.0 V_{P-P}$)
- Output Current 120 mA
- Pin Compatible with AD8001, TSH350, OPA681
- This is a Pb-Free Device

Applications

- High Resolution Video
- Line Driver
- High-Speed Instrumentation
- Wide Dynamic Range IF Amp
- Set Top Box
- NTSC/PAL/HDTV




Figure 1. Frequency Response:
Gain (dB) vs. Frequency
 $A_V = +2.0$




ON Semiconductor[®]

<http://onsemi.com>




**SOT23-5
(TSOP-5)
SN SUFFIX
CASE 483**

MARKING DIAGRAM



YB1 = NCS2511
A = Assembly Location
Y = Year
W = Work Week
▪ = Pb-Free Package

SOT23-5 (TSOP-5) PINOUT



ORDERING INFORMATION

Device	Package	Shipping [†]
NCS2511SNT1G	SOT23-5 (TSOP-5) (Pb-Free)	3000/Tape & Reel

[†]For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.